

Multimatic Air Star Hybrid Class

Designed for environmentally friendly solvents!



Dual Cleaning Method

- * **Full Immersion**
- * **Spray Jet**



- * No Water Necessary
- * Lower Your Utility Costs
- * Can Be Used With or Without Steam
- * 2 Separate Filter Systems
- * High Efficiency Air Cooling System
- * No Distillation Required
- * Refrigerated Solvent Cooling (Air Cooled Models)
- * Stainless Steel Construction
- * Simple, Easy Installation
- * Exclusive Multimatic MultiComp III Computer



Multimatic

162 Veterans Drive, Northvale, NJ 07647/USA
Telephone 201-767-9660 • Fax: 201-767-7037

SPECIFICATIONS

Multimatic AirStar

MODEL	AS40	AS65
BASKET		
Capacity (lbs. Maximum)	40	65
Volume, cu. ft.	12.5	22
Diameter, in.	37.5	44
Depth, in.	19.5	26
Cleaning Speed, rpm	40	34
Extraction Speed	575	550
TANKS		
Work Tank I (gallons)	57	84
Work Tank II (gallons)	57	84
FILTER*		
Cartridges (split)	6	12
MACHINE DIMENSIONS		
Width, in.	77.2	89
Depth, in.	54	72
Height, in.	90	95.5
Machine with Tray, in.	79 x 59 x 94	91 x 75 x 99.5
<i>Partially dismantled for clearance</i>		
Depth x Height, in.	49 x 79	62 x 84
FLOOR LOAD		
Weight, lbs. (without solvent)	2203	4846
POWER REQUIREMENTS, STEAM HEATED		
Max. Operating Load, amps	40	50
Motor		
Drive, HP	5	10
Solvent Pump, HP	1	1.5
Drying Fan, High Speed HP	3.4	3.4
Refrigeration Compressor, HP	5.0	8.0
SUPPLY CONNECTIONS		
Compressed Air		
Pressure, psi	85-95	85-95
Size of Fitting, in.	1/4	1/4
Steam (Where used to provide most efficient operation)		
Pressure, psi	45-60	45-60
Size of Fitting, in.		
Steam Inlet	1/2	1/2
Condensate Return	1/2	1/2
Water Required on water-cooled models		
Pressure, psi	45-85	45-85
Size of Fitting, in.		
Water Inlet	1	1
Water Outlet	1	1
ELECTRICAL REQUIREMENT	208-220/60/3	208-220/60/3

All Specifications Subject to Change Without Notice
*Available with either spin disc or cartridge filtration

RIB-MAY 2009



Multimatic

162 Veterans Drive, Northvale, NJ 07647/USA
Telephone: 201-767-9660 • Fax: 201-767-7037